

present invention as the following. This is kindly noted by the Examiner.  
From the mark-up version appended, it is appreciated that no new matter  
has been incorporated therein.

5. PLEASE AMEND THE SECOND PARAGRAPH IN PAGE 2 OF  
THE SPECIFICATION

In accordance with one aspect of the invention, there is  
provided an electric door lock comprising a housing, a handle  
rotatably attached to the housing, a lock device engaged in the  
housing, a follower received in the housing and secured to the  
10 handle, to rotatably secure the handle to the housing, an  
electromagnetic control device including a receptacle rotatably  
received in the follower, a plunger slidably engaged in the  
receptacle and extendible out of the receptacle to engage with the  
15 follower, and a latching device for selectively latching the plunger  
to the receptacle, and to maintain an engagement of the plunger  
with the follower, and to allow the receptacle of the  
electromagnetic control device to be selectively latched to the  
follower with the selectively latching device, and a connecting  
20 device for selectively connecting the lock device to the plunger,  
to selectively latch the plunger to the receptacle ~~and to the~~  
~~receptacle~~, and to allow the receptacle of the electromagnetic  
control device to be selectively latched to the follower with the  
selectively connecting device.

25

PLEASE AMEND THE THIRD PARAGRAPH IN PAGE 8 OF THE  
SPECIFICATION

A coil spring 47 (FIGS. 5, 5A) may be engaged in the barrel 40 and engaged with the bar 45, to bias the bar 45 against the barrel 40, and to stably retain the bar 45 in either the higher seats 43 (FIGS. 5, 7) or the lower seats 44 (FIGS. 5A, 6) of the barrel 40. A catch 48 is secured to or extended from the bar 45 (FIGS. 6 and 7), and moved in concert with the bar 45 ~~54~~, and a spring 49 may further be provided and engaged onto the catch 48.

PLEASE AMEND THE SECOND PARAGRAPH IN PAGE 9 OF  
THE SPECIFICATION

The follower 50 further includes a hole 54 formed therein (FIG. 3) to receive the catch 48. The spring 49 may thus be biased between the follower 50 and the bar 45. The follower 50 further includes a wall 55 provided thereon or extended therefrom and having a passage 56 formed therein. An electromagnetic control device 60 is rotatably engaged on or received in the wall 55, and includes a plunger 80 slidably received in a receptacle 62 and extendible ~~out of the plunger 80~~ to selectively engage into the passage 56 of the wall 55 of the follower 50 (FIG. 2).